**REMARKS** 

Claims 1-11 as originally filed in the PCT application have been canceled herein, and

the subject matter thereof represented as new claims 12-27. The new claims conform to

regular U.S. practice by eliminating multiple dependencies.

In addition, a substitute specification is included herewith to conform to regular U.S.

practice. Headings have been inserted, clarification has been made for the purposes of

making grammatical sense and for proper English. No new matter is introduced hereby.

A marked up version showing the changes made is also attached. Applicant respectfully

requests that the amendment and substitute specification be entered.

Respectfully submitted,

Volker BRASS et al.

Dawrouce A. Maxham
Attornevs for A

Reg. No. 24,483

THE MAXHAM FIRM

**Symphony Towers** 

750 "B" Street, Suite 3100

San Diego, California 92101

Telephone: (619) 233-9004

Facsimile: (619) 544-1246

9

### ADDITIONAL INFORMATION FOR VOICE GROUP CALL SERVICE

## **Background**

#### 5 1. Field of the Invention

The present invention generally relates to the field of voice group services in mobile communication networks, and in particular to Voice Group Call Services (VGCS).

10

15

20

25

### 2. Discussion of Prior Art

Voice Group Call Service allows the establishment of a call between members of a group in numerous cells of the mobile telecommunication network simultaneously. These cells define the service area. All subscribers belonging to the group have the possibility to listen to the call in the service area. It is also possible to participate in the call individually. Service subscribers of the radio network can become group members on a network widenetwork-wide basis to one or more groups pre-defined in the network by a corresponding group identification (group ID). The membership enables them to receive voice group calls associated with that group ID.

In addition, certain group members are entitled by their subscription to initiate Voice Group Calls (VGC). In addition to subscriber details in the Home Location Register (HLR), it is necessary for the mobile station (MS) to be aware of its group membership by storing details on the Subscriber Identity Module (SIM). This is required because it responds to notification messages which include only the group call relevant information, (i.e. no IMSI or TMSI details). information, that is, no IMSI or TMSI details. Having become a group member, each service subscriber can set to active state or deactive state the group ID or any one out of his several group IDs on the SIM. In active state the subscriber can initiate VGCs to that group ID. When in deactive state the

30

subscriber can not cannot make VGCs to the group and the mobile station ignores any notification for that group ID.

5

10

15

20

25

30

A group call area can be restricted to a single Mobile Switching Center (MSC) area or can exceed one MSC area (implementation option). A voice group call is initiated by a calling subscriber by a related man machine interface action for the service selection and the group ID dialed. The MSC in which the voice group call is initiated obtains by requesting a Group Call Register GCR (GCR) the group call attributes. The GCR is functionality in the network containing the group call attributes. This GCR interrogation after call initiation also determines whether the MSC acts as group call Anchor- or as group call Relay-MSC. A group call Anchor-MSC is responsible for managing and maintaining a particular VGC. The group call Anchor-MSC is determined as the one controlling the cells of the group call area. For VGCSs where the group call area exceeds an MSC area, the group call Anchor-MSC is predefined in the network. A group call Relay-MSC controls cells of a group call area which are not under control of the group call Anchor-MSC for those voice group call services where the group call area exceeds one MSC area.

If the MSC is not the Anchor-MSC then the call will be "forwarded" from the Relay-MSC to the respective Anchor-MSC (information also delivered by GCR) and further "call-establishment" is done by the Anchor-MSC.

When a calling subscriber (talker) initiates a voice group call, one voice group call channel is established in each cell of the group call area and notifications for that call is sent in each of these cells. A voice group call channel is a downlink to be allocated in each cell of the group call area for a particular voice group call. All mobile stations being service subscribers for that Voice Group Call in one cell listens to the common downlink. All mobile stations of the listening service subscribers in one cell only listens to the same common downlink (voice group call channel). Of course it is possible to change the talker at any time, so that one of the listeners of the group becomes the talker and the previous

talker becomes a listener.

10

15

20

25

30

The standards of Voice Group Call Service are specified in the technical specification ETSI TS 143 068, V5.2.0, December 2002: Digital Cellular telecommunication system (Phase 2+); Voice Group Call Service (VGCS); Stage 2; 3GPP TS 43.068 version 5.2.0 Rel. 5.

US patent publication 2003/0100326 A1 relates to a group location and route sharing system for communication units in a trunked communication system, wherein the communication units are engaged in a group voice call communication. Subscription and location data can be sent as a supplementary information to the group voice call communication by using an underlying packet transport layer.

**SUMMARY OF THE INVENTION** 

It is the object a purpose of the invention to enhance the conventional voice group call service by providing an additional communication service without changing the general architecture of the communication network.

This object is achieved by providing a method and a communication system as disclosed in the independent claims.

Other features which are considered to be characteristic for the invention are set forth in the appended claims.

The additional information for Voice Group Call Service (VGCS) is designed to provide all active members of a VGCS in parallel, i.e. parallel, that is, simultaneous to an ongoing voice group call, with additional information, for example example, the tactical addresses of the current talker. The information contained 25-here may have a text-oriented or binary-oriented character.

The transmission of the additional information shall be realized only in acknowledged mode and is sent on the Slow Associated Control Channel (SACCH), which represents an associated control channel for the downlink traffic channel of the voice group call.

5

#### **BRIEF DESCRIPTION OF THE DRAWING**

The objects, advantages and features of the invention will be more clearly perceived from the following detailed description, when read in conjunction with the accompanying drawing, wherein:

In the following the invention will be described with reference to the appended drawings.

Fig.1 Figure 1 shows a functional voice group call architecture with a group call register; and

15

10

Fig. 2 Figure 2 shows a transfer of additional information to members of a VGCS.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20

The general architecture of GSM is maintained in this invention. In—With reference to Fig. 1, in addition, a network function is required which is used for registration of the group call attributes, the group call register (GCR) 10a, 10b, 10c. The GCR function is mainly a database function, holding information about voice group calls. The signalling between the entities shown in figure iFig. 1 shall be as defined in the following.

25

The Mobile Switching Center (MSC) 12a, 12b, 12c containing the cell within which this voice group call is initiated performs subscription checking against Visitor Location Register (VLR) 14a, 14b, 14c and Home Location Register 16 records. It then consults its GCR 10a, 10b, 10c, respectively, to determine the group call attributes related to its MSC area and whether it is the group call Anchor-MSC 12a for that voice group call. If it is not, the GCR provides with the group call reference and the routing

information identifying the group call Anchor-MSC 12a to the originating MSC. The originating MSC then routes the voice group call to the Anchor-MSC 12a. If the originating MSC is the group call Anchor-MSC 12a, along with the group call attributes, the respective GCR 10a provides information on all group call Relay-MSCs 12b, 12c to be involved. The group call Anchor-MSC 12a sets up links to all group call Relay-MSCs 12b, 12c. Each MSC 12a, 12b, 12c involved in a voice group call obtains its proper group call attributes from the GCR 10a, 10b, 10c related to the respective MSC.

The GCR 10a, 10b, 10c holds for a related MSC area for each group ID and cells from which voice group calls can be established by service subscribers the subscribers, the group call reference to be used for a voice group call to be established and an indication whether the originating MSC is the group call Anchor-MSC 12a. If the originating MSC is the group call Amchor-MSC 12a, the GCR 10a provides the group call attributes related to that group call reference to the originating MSC and the originating MSC establishes the voice group call. If the originating MSC is not the Anchor-MSC 12a, the GCR 10a provides the group call reference plus the routing information identifying the Anchor-MSC 12a to the originating MSC and the originating MSC routes the voice group call to the Anchor-MSC 12a.

According to the invention, an additional information can be forwarded to all group members during an ongoing voice group call. This is preferably done by transmitting a message containing the additional information on the associated control channel for the traffic channel of the voice group.

The Referring now to Fig. 2, the MSC 12 (either Anchor- or Relay-MSC) triggers via an appropriate message, e.g. anfor example, an additional-information-request-message, on the A-interface the base station subsystem (BSS) 20 to send the additional information to the mobile stations MS 22, 24 of the group members, i.e. onethat is, one talker 22 and at least one listener 24. The message contains at least the additional information itself. The VGC-ID or VGC-Reference represents an optional part of this message.

In the case where the message is sent on the controlling SCCP-connection (Signalling Connection Control Part connection) of the VGC, the addressing which VGC is meant is not necessary.

In addition to this, the message, i.e. the that is, the additional-information-requestmessage, can be sent on the resource controlling SCCP-connections.

Afterwards, the BSS 20 transmits the additional information on the SACCH of all TCHs where the VGC is ongoing, so that the additional information can be received by all MS 22, 24 participating in the voice group. The provisioning of the additional information in radio cells which are belonging the VGC-area but in which a VGC-channel is not established is not necessary.

In the case that the additional information is sent on the controlling SCCP-connection, the BSS 20 is responsible to transmit the additional information on all SACCHs for this VGC.

15

20

After having sent the additional information, the BSS 20 provides an acknowledge information to the MSC 12 that the additional information was sent to the mobile stations 22, 24. However, this acknowledge information does not confirm to the sender of the message that the individual members of a voice group call have received the message.

In order to give an indication that the additional information was at least received by the current talker 22, the talker 22 may send an acknowledgement on the Uplink-SACCH for this VGC.

# List of Reference numerals and abbreviations

10a, 10b, 10c	Group Call Register
12a, 12b, 12c	Mobile Switching Center
14a, 14b, 14c	Visitor Location Register
16	Home Location Register
18	<b>Gateway Mobile Switching Center</b>
20	Base Station Subsystem
22	MS (Talker)
24	MS (Listener)

BSS Base Station Subsystem

MS Mobile Station

MSC Mobile Switching Centre

SACCH Slow Associated Control Channel
SCCP Signaling Connection Control Part

TCH Traffic Channel

VGC Voice Group Call

VGCS Voice Group Call Service